

Portable Foam



Note:

Model FX6, FX9 and FX100 are SASO Approved

SFECO Portable Foam Fire Extinguishers are characterized for their quick fire suppression and extinguishing capabilities, especially oil, petrol and other liquid fire.

It works by covering a burning flammable liquid with a blanket of foam, cutting off the fire's air supply and preventing the release of flammable vapours.

Portable foam extinguishers are generally used as first attack fire fighting units which are suitable for class A and B fires.

Class of Fire



A Solid matters forming glowing residues. e.g. wood, rubber (car tires), paper, textiles.



B Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.

Model	FX6	FX9	FX100	FXC100
Capacity	6 Ltr	9 Ltr	10 Ltr	10 Ltr
Total Weight (Kg)	9.58	14.4	16	14.8
Total Height with Base (mm)	605	645	630	630
Total Width (mm)	210	210	210	240
Cylinder Height (mm)	510	540	540	615
Cylinder Diameter (mm)	150	185	185	185
Hose Length (mm)	480	625	625	650
Maximum Effective Range (m)	5-6	5-6	5-6	5-6
Duration of Discharge (Sec)	25-30	30-40	35-45	50-60
Extinguishing Agent	AFFF	AFFF	AFFF	AFFF
Propelling Agent	N ₂ /Air	N ₂ /Air	N ₂ /Air	CO ₂
Working Pressure	12-15 Bar			
Testing Pressure	30 Bar			
Coating	Electrostatic Polyester Powder			
Storage Temperature	5°C to 60°C			

Special Internal Coating



The Internal part of the extinguisher has been coated with special plastic coat, integrated by Whirl Sintering process.



CAUTION:

NOT FOR USE ON LIVE ELECTRICAL EQUIPMENT

In line with our policy of continuous product improvement, SFECO reserves the right to modify specifications without prior notice.