

SERIES 3500 & 3600 WHEELED EXTINGUISHERS

DRY CHEMICAL TYPE

Red glossy polyester coated steel cylinder, carriage and hose hanger assembly. Quick release, non-kink hose with positive grip nozzle. Semi-pneumatic tires. Size, agent, and method of operation as selected by figure number.

HALOTRON TYPE

Red glossy polyester coated steel DOT cylinder, carriage, and hose rack. Quick opening chrome plated brass valve. FAA approved as clean agent for both ramp use and onboard aircraft.

CARBON DIOXIDE TYPE

Red glossy polyester coated steel cylinder, black carriage. Quick release, non-kink hose with shock resistant, rubber insulated horn and handle. Diffusion tip and safety release disc in discharge valve. Pressurized content is a non-contaminating, non-conductive odorless gas. Semi-pneumatic tires. Sizes as selected by figure number.

WHEEL MODEL SELECTION

- ☐ 3500 SERIES Dry Chemical
- ☐ 3560 SERIES Halotron 1
- ☐ 3600 SERIES Carbon Dioxide



PRODUCT OPTIONS

NO AVAILABLE OPTIONS

EXTINGUISHER MODEL SELECTION

- ☐ 3510 ABC Stored Pressure Multi-Purpose Dry Chemical
- ☐ 3520 ABC Nitrogen Cylinder Operated Multi-Purpose Dry Chemical
- ☐ 3525 ABC Stored Pressure Multi-Purpose Dry Chemical
- ☐ 3530 BC Stored Pressure Purple-K Dry Chemical
- ☐ 3540 BC Nitrogen Cylinder Operated Purple-K
 - Dry Chemical
- ☐ 3550 BC Nitrogen Cylinder Operated Dry Chemical
- ☐ 3560 65 lb. Stored Pressure Halotron 1
- ☐ 3565 150 lb. Stored Pressure Halotron 1
- 3610 BC Self Expellent Carbon Dioxide
- ☐ 3620 BC Self Expellent Carbon Dioxide

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer-Fire Pro, Member of Morris Group International The Please visit potterroemer.com for most current specifications.















POTTER ROEMER

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473

www.potterroemer.com



SERIES 3500 & 3600 WHEELED EXTINGUISHERS

MODEL DIMENISIONS

Model No.	Туре	Agent	Function	Size (lbs.)	Method of Operation	UL/Rating	H E I G H T	W I D T H	D E P T H	Hose Length
3510	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		50 lb.	SP	20A:160B:C	46"	21-1/2"	24"	25'
3520	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		125 lb.	NC	30A:240B:C	45"	24"	36"	50'
3525	ABC Multi-purpose Dry Chemical	Ammonium Phosphate		125 lb.	SP	30A:240B:C	53-1/2"	28"	40"	50'
3530	Purple-K Dry Chemical	Potassium Bicarbonate		50 lb.	SP	160B:C	46"	21-1/2"	24"	25'
3540	Purple-K Dry Chemical	Potassium Bicarbonate		125 lb.	NC	320B:C	45"	24"	36"	50'
3550	Dry Chemical	Sodium Bicarbonate		150 lb.	NC	240B:C	58"	28"	39-1/4"	50'
3560	Halotron 1	Halotron		65 lb.	SP	4A:80BC	58"	28"	39"	50'
3565	Halotron 1	Halotron		150 lb.	SP	10A:120BC	64"	30"	42"	50'
3610	Carbon Dioxide	Carbon Dioxide		50 lb.	SE	20B:C	47"	23"	48"	40'
3620	Carbon Dioxide	Carbon Dioxide		100 lb.	SE	20B:C	47"	23"	48"	40'

NOTE: 3620 provided with two cylinders.

METHOD OF OPERATION: SP = Stored Pressure

NC = 23 Cubic Foot Nitrogen Cylinder with Handwheel valve

SE = Self Expellent







3600 SERIES

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer-Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

3500&3600 SERIES



NFPA











POTTER ROEMER

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473

www.potterroemer.com