



Note:

Model TC10, TC25 and TC30 are SASO Approved

SFFECO Mobile carbon dioxide fire extinguishers are known for its high reliable performance. The cylinders of CO₂ fire extinguishers are seamless and are extruded from high grade Chrome Molybdenum Steel or Manganese or Carbon Steel.

Suitable to use on Class B and Electrical fires.

The CO₂ extinguisher is especially effective on electrical fires because, being a gas; it does not leave any residues which might further harm the damaged equipment.

Class of Fire



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.

Model	TC10	TC25	TC30	TCB100
Capacity	10 Kg	25 Kg	30 Kg	45.5 Kg
Total Weight	38 Kg	96 Kg	102 Kg	124.6 Kg
Total Height (mm)	1025	1420	1420	1650
Total Width (mm)	440	590	590	590
Total Depth (mm)	940	1310	1310	1500
Hose Length (mm)	3500	3500	3500	6000
Maximum Effective Range (m)	4	6	6	6
Duration of Discharge (Sec)	40-50	75-80	90-94	110-120
Extinguishing Agent	CO ₂			
Testing Pressure (Bar)	250			
Coating	Electrostatic Polyester Powder			
Storage Temperature	-20°C to +60°C			

In line with our policy of continuous product improvement, SFFECO reserves the right to modify specifications without prior notice.