



**Note:**

Model TF25, TF50, TF100 and TFC35G are SASO Approved

SFFECO Mobile Foam Fire Extinguisher, available in stored pressure model (TF) and external high pressure CO2 cartridge model (TFC). Manufactured using special cold rolled steel and the cylinder is painted with electrostatic polyester powder.

This unit is easy to use and can be used by one person, suitable to keep in factories and warehouses, as well as petrol stations. The AFFF will quickly seal the surface of a liquid fire to prevent re-ignition.

## Class of Fire



**A** Solid matters forming glowing residues. e.g. wood, rubber (car tires), paper, textiles.



**B** Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.

## CAUTION:

NOT FOR USE ON LIVE ELECTRICAL EQUIPMENT



Model	TF25	TF10G	TF50	TF100	TF35G	TFC50	TFC100	TFC35G
Capacity	25 Ltr	37.8 Ltr	50 Ltr	100 Ltr	132 Ltr	50 Ltr	100 Ltr	135 Ltr
Total Weight	51.5 Kg	63 Kg	82 Kg	151 Kg	202 Kg	93 Kg	175 Kg	219 Kg
Total Height (mm)	990	1120	1010	1100	1341	1010	1100	1341
Total Width (mm)	455	450	555	700	555	555	700	700
Total Depth (mm)	665	400	695	900	1078	695	900	1078
Hose Length (mm)	3000	3000	5000	5000	5000	5000	6500	6500
Maximum Effective Range (m)	8	8	8	8	8	8	8	8
Duration of Discharge (Sec)	19-23	29-33	38-42	77-82	100-105	42-45	82-85	110-120
Extinguishing Agent	AFFF	AFFF	AFFF	AFFF	AFFF	AFFF	AFFF	AFFF
Propelling Agent	N <sub>2</sub>					CO <sub>2</sub>		
Working Pressure	12-15 Bar							
Testing Pressure	30 Bar							
Coating	Electrostatic Polyester Powder							
Storage Temperature	5°C to 60°C							

In line with our policy of continuous product improvement, SFFECO reserves the right to modify specifications without prior notice.