



Note:

Model WH600, WH900 and WH1000 are SASO Approved

SFECO Water Extinguishers are characterized by their high performance, simple method of operation ideal for tackling freely burning materials such as paper, cloth, wood and furniture.

These are good general purpose fire extinguishers and widely used and are very useful, cost-effective and relatively easy to clean up. It cools burning materials by absorbing heat. Effective on class A fires.

Class of Fire



A Solid matters forming glowing residues. for example: wood, rubber (car tires), paper, textiles.

Model	WH600	WH900	WH1000	WHC1010
Capacity	6 Ltr	9 Ltr	10 Ltr	10 Ltr
Total Weight (Kg)	9.58	14.4	16.8	17
Total Height with Base (mm)	605	645	630	630
Total Width (mm)	210	210	240	255
Cylinder Height (mm)	510	540	540	615
Cylinder Diameter (mm)	150	185	185	185
Hose Length (mm)	480	625	625	580
Maximum Effective Range (m)	5-6	5-6	5-6	5-6
Duration of Discharge (Sec)	25-30	30-40	35-45	50-60
Propelling Agent	N ₂ /Air	N ₂ /Air	N ₂ /Air	CO ₂
Extinguishing Agent	Water			
Working Pressure	12-15 Bar			
Testing Pressure	30 Bar			
Coating	Electrostatic Polyester Powder			
Storage Temperature	5°C to 60°C			

Special Internal Coating



The Internal part of the extinguisher has been coated with special plastic coat, integrated by Whirl Sintering process.



CAUTION:

NOT FOR USE ON LIVE ELECTRICAL EQUIPMENT