

SERIES 4036-FA5 & 4038-FA5 REG-U-MATIC® ADJUSTABLE PRESSURE REDUCING CONTROL VALVES

FEATURES

Reduces pressure under flow and no flow conditions
Static pressure rated up to 340 PSI (23.4 BARS)
Flow rated up to 500 GPM (1893 LPM)
4 pressure gauge taps on both inlet and outlet
Built in automatic check valve
Downstream pressure rating 65-175 PSI (4.5 BARS to 12 BARS)
UL listed, complies with NFPA-13

MODEL SELECTION

MODEL 4036-FA5 & 4038-FA5

Brass valve with non-rising stem and indicator bonnet.
internal parts of brass and stainless steel, red alloy
handwheel, 2 1/2" Female N.P.T. x Male hose threads. Listed
by Underwriters Laboratories as a checking device.


NOTE: The in-line installation of a "REG-U-MATIC" sets up a closed system. A
relief valve should be installed to eliminate excessive pressure build up due to
line surges.




**RATED
400 PSI**



MODEL 4036-FA5 (Shown)



4036-FA5



4038-FA5

PRODUCT OPTIONS

FINISHES:

☐ -C Rough Chrome Plated

OPTION:

☐ -MSA Monitor Switch Adapter
☐ -GRV Grooved Connections

Model No.	A		B Closed		B Open		C		D		E	
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
4036-FA5	7 7/8	200	13 25/64	353	13 3/16	335	7 7/8	200	1 31/32	50		
4038-FA5	7 7/8	200	17 1/2	445	17 1/2	445	3 15/32	88	3 15/32	88	7 7/32	183

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

4036-FA5&4038-FA5 SERIES Date: 10/24/24

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



POTTER ROEMER

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com

SERIES 4036-FA5 & 4038-FA5 REG-U-MATIC® ADJUSTABLE PRESSURE REDUCING CONTROL VALVES

VALVE SETTING INSTRUCTIONS:

Direction of water flow is to be as shown by the indicating arrow on the valve. For installation requirements refer to NFPA 13 for sprinkler systems.

These valves are to be set to provide outlet pressures and flows in accordance with NFPA 13 and tested periodically in accordance with NFPA 25.

To adjust the valve setting:

1. Refer to the graphs provided and select the appropriate setting. After selecting the appropriate GPM, go up on the graph from the Residual Inlet Pressure. At the setting number (100, 140, 175) view the Residual Outlet Pressure on the vertical side of the graph.
2. A rod key included with the valve, shall be used. The rod key is inserted into the valve cylinder.
3. Rotate the cylinder with the rod key, until the desired setting is aligned with the indicating arrow on the valve.
4. The valve is now set.
5. As the valve is automatic, the system must be flushed thoroughly to ensure that all debris is removed from the piping.
6. The rod key used to adjust the valve setting should be given to responsible personnel at the installation location, who should be instructed in its use if an emergency adjustment is necessary.

The valve should also be tagged with information stating where the rod key can be located.

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

4036-FA5&4038-FA5 SERIES

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.




POTTER ROEMER

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com

SERIES 4036-FA5 & 4038-FA5 REG-U-MATIC® ADJUSTABLE PRESSURE REDUCING CONTROL VALVES



Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

4036-FA5&4038-FA5 SERIES

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



POTTER ROEMER

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com