

SERIES 4080-4095 PRESSURE RESTRICTING HOSE VALVES

For Use with a Fire Hose Rack Assembly or as a Fire Department Outlet Connection.

PRESSURE RESTRICTING HOSE VALVES: Cast brass valve with red handwheel. Water pressure is controlled by adjustable flow restriction. If full flow is required, the restriction may be overridden. Female NPT inlet by Female NPT or Male Hose Thread outlet. 175psi rated. Furnished with field setting chart.

MODEL SELECTION

Male Outlet Valves:

4080 1-1/2" Adjustable Pressure Restricting Valve

Buy American

☐ 4080-P 1-1/2" Adjustable Pressure Restricting Valve

Domestic Manufactured

■ 4080-PR 1-1/2" Adjustable Pressure Restricting Valve

4085 2-1/2" Adjustable Pressure Restricting Valve

Buy American

☐ 4085-P 2-1/2" Adjustable Pressure Restricting Valve

Domestic Manufactured

☐ 4085-PR 2-1/2" Adjustable Pressure Restricting Valve

Female Outlet Valves:

1-1/2" Adjustable Pressure Restricting Valve **4090**

Buy American

☐ 4090-P 1-1/2" Adjustable Pressure Restricting Valve

Domestic Manufactured

☐ 4090-PR 1-1/2" Adjustable Pressure Restricting Valve

4095 2-1/2" Adjustable Pressure Restricting Valve

Buy American

☐ 4095-P 2-1/2" Adjustable Pressure Restricting Valve

Domestic Manufactured

☐ 4095-PR 2-1/2" Adjustable Pressure Restricting Valve

OPTIONAL CAPS & FLANGES

☐ 4615 1-1/2" Cap w/ Chain

☐ 4625 2-1/2" Cap w/ Chain

☐ 4711 1-1/2" Flange 3" O.D.

☐ 4712 2-1/2" Flange 6-1/4" O.D.



PRODUCT OPTIONS

FINISHES:

□ -B Polished Brass

□ -C Rough Chrome Plated

□ -D Polished Chrome Plated

THREADS:

☐ N.S.T.

☐ Other

VARIATIONS:

☐ Rocker Lugs (Cap Models Only)

☐ -GRV Grooved Inlet

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.











POTTER ROEMER

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890

Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473

www.potterroemer.com




SERIES 4080-4095 PRESSURE RESTRICTING HOSE VALVES


MODEL DIMENSIONS

Model	Size	Α	В	C-Closed	C-Open	D	E
4080	1-1/2"	2-1/4"	4-1/32"	6-1/2"	7-19/32"	2-1/2"	1-7/8"
4080-P	1-1/2"	2-7/32"	3-3/4"	6-13/16"	7-27/32"	2-7/16"	1-13/16"
4080-PR	1-1/2"	2-13/32"	4"	6-13/16"	7-7/8"	2-13/32"	2"
4085	2-1/2"	3"	5-1/8"	8-29/32"	10-19/32"	3"	2-5/8"
4085-P	2-1/2"	3-7/32"	5"	9-21/64"	11-3/8"	3-19/32"	2-19/32"
4085-PR	2-1/2"	3-15/64"	4"	9-21/64"	11"	3-15/64"	2-3/4"
4090	1-1/2"	2-5/32"	4-1/32"	6-1/2"	7-19/32"	2-1/2"	1-7/8"
4090-P	1-1/2"	2-13/64"	3-3/4"	6-13/16"	7-27/32"	2-13/32"	1-13/16"
4090-PR	1-1/2"	2-13/32"	4"	6-13/16"	7-7/8"	2-13/32"	2"
4095	2-1/2"	3-5/32"	5-1/8"	8-29/32"	10-19/32"	3"	2-5/8"
4095-P	2-1/2"	3-3/16"	5"	9-21/64"	11-3/8"	3-9/16"	2-21/32"
4095-PR	2-1/2"	3-15/64"	4"	9-21/64"	11"	3-15/64"	2-3/4"









MODEL 4080-4085

MODEL 4090-4095

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.

4080-4095 SERIES















POTTER ROEMER

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890

Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473

www.potterroemer.com