

## Conventional MCP compact, small, red, with glass pane, IP 66/67



### Features:

- High IP protection class IP 66 / 67
- Integrated loop isolator
- Triple key function (test, open, reset)
- Plug-in connection clamps
- Detectors that are not ready for operation can be marked with the "out of order" label by reversing the enclosed glass pane

**Part-No.: 804960**

**Approval: VdS**

Waterproof MCP including housing and alarm indicator. For connection to a conventional detection zone.

### Common technical data

Operating voltage	8 ... 30 V DC
Quiescent current @ 9 V DC	0 µA
Alarm current @ 9 V DC	9 mA
No. of detector/zone	10 detectors per zone (according to VdS)
Alarm display	red LED and yellow actuation indicator
Connection terminal	max. 2.5 mm <sup>2</sup> (AWG 26-14)
Application temperature	-40 °C ... 70 °C
Storage temperature	-40 °C ... 75 °C
Air humidity	< 95 %
Type of protection	IP 66 / IP 67
Housing	PC ASA plastic
Color	red, similar to RAL 3020
Weight	approx. 110 g
Detector specification	EN 54-11, type A
Dimensions	W: 88 mm H: 88 mm D: 21 mm



Use M20 cable glands with 15 mm connecting thread length and sealing ring, e.g. blueglobe by Pflitsch (Screw joint Part No.: bg 820PA/sealing ring part no.: DRF 220).



1 x Spare glass 704960 1 x Plastic spare key 704966 1 x Transparent cover 1 x Surface mount housing