

DS-2CE10UF3T-LSYE 4K Smart Hybrid Light ColorVu Fixed Mini Bullet Camera



- High quality imaging with 4K, 3840 × 2160 resolution
- 24/7 color imaging with F1.0 aperture
- Smart-Hybrid light, optimize your security with flexible lighting options
- Clear imaging against strong back light due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- Up to 20 m white light and 30 m IR distance for bright night imaging
- Built-in mic, high quality audio with audio over coaxial cable
- Water and dust resistant (IP67)
- Anti-corrosion design, providing reliability and longevity compared to standard (NEMA4X)

▪ Specification

Camera	
Image Sensor	4K CMOS
Max. Resolution	3840 (H) × 2160 (V)
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/12.5 s to 1/50,000 s;NTSC: 1/15 s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm fixed focal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 105°, vertical FOV: 60°, diagonal FOV: 132° 3.6 mm, horizontal FOV: 90°, vertical FOV: 50°, diagonal FOV: 112°
Lens Mount	M16
Microphone	
Pickup Distance	In a radius of up to 5 m
Amount	1
Illuminator	
Supplement Light Type	Smart,IR,White Light
Supplement Light Range	IR: Up to 30 m, White Light: Up to 20 m
Image	
Image Parameters Switch	STD/HIGH-SAT/HIGHLIGHT
Image Settings	Saturation,Brightness,Contrast,Sharpness,Anti-banding,AGC
Frame Rate	TVI: 4K @12.5/15 fps, 3K@25/20 fps, 4 MP@25 fps/30 fps, 1080p@25 fps/30 fps
Day/Night Mode	Auto/Color
Wide Dynamic Range (WDR)	≥130 dB
Image Enhancement	BLC,HLC,Global,WDR,Face AE,HLS
Privacy Mask	4 programmable polygon privacy masks
Noise Reduction	3D DNR
White Balance	Auto,Manual
Interface	
Video Output	1 HD analog output
Event	
Motion Detection	4 programmable motion areas
General	
Power	12 VDC±25%/PoC.at, Max. 7 W, *You are recommended to use one power adapter to supply the power for one camera.
Material	Metal
Dimension	172.9mm × 69.1 mm × 66 mm (6.81" × 2.72" × 2.59")
Weight	Approx. 460 g (1.01 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F). Humidity 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English


Approval	
Protection	IP67
Anti-Corrosion Protection	NEMA 4X (NEMA 250-2018)

▪ Available Model

DS-2CE10UF3T-LSYE(2.8mm)

DS-2CE10UF3T-LSYE(3.6mm)

▪ Dimension






Unit: mm (inch)

▪ Accessory

▪ Optional

DS-1275ZJ-SUS	DS-1276ZJ-SUS	DS-1280ZJ-XS
		

▪ Installation Methods

Vertical Pole Mounting DS-1275ZJ-SUS+DS-1280ZJ-XS	Corner Mounting DS-1276ZJ-SUS+DS-1280ZJ-XS	Junction Box DS-1280ZJ-XS
		

See Far, Go Further



www.hikvision.com
support@hikvision.com

