### UL Product iQ®

# Model 730

File Number: EX27358



#### **COMPANY**

#### **Bermad UK LTD**

Unit 8 Hungerford Trading Estate Smitham Bridge Rd Hungerford Berkshire, RG17 0QP United Kingdom

#### **MODEL INFO**

730

ATTRIBUTES AND RATINGS				
Body Type	Nom Pipe Size, NPS	End Configuration	Max Relief (Set) Pressure, psig (kPa)	
Angle	8	Flanged by Flanged	175 (1206)	
Angle	2, 2-1/2, 3, 4, 6	Flanged by Flanged, Threaded by Threaded, Flanged by Threaded	350 (2413)	
Globe	8	Flanged by Flanged	175 (1206)	
Globe	2, 2-1/2, 3, 4, 6	Flanged by Flanged, Threaded by Threaded, Flanged by Threaded	350 (2413)	

#### **GENERAL**

#### **Installation Limitations**

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

 $\blacksquare$ 





Valves | Water Pressure Relief Valves | Valves, Water Relief

## **Models FP730-**UL/FM, FP430-UL/FM

### **Product Description**

Model FP730-UL/FM, sizes 2, 3, 4, 6 and 8 in. NPS, rated working pressure 200 psi (1380 kPa).

Model FP430-UL/FM, sizes 2, 3, 4 and 6 in. NPS, rated working pressure 175 psi (1205 kPa).

2 and 3 in. size valves available with threaded connections (NPT and BSPT), 3 through 8 in. size valves available with flanged or grooved end connections.

Limited to installations having split-case centrifugal fire pumps mounted horizontally or vertically.

### **Details**

Category	Valves, Water Relief
Class of Work	1361 - Water Pressure Relief Valves
Approval Standard	FM 1361 - Water Pressure Relief Valves
Certification Type	FM Approved
Listing Country	United States of America

# **Company**

Bermad Inc. 10600 Telge Road, Suite 200, Houston, Texas 77095 United States of America http://bermad.com